

KÁCSA[®] AUDIO

SINCE · 1995 · ALAPÍTVÁ

KáCsa[®] Cables product line of cables

February 2011

Page 2 - 3	KáCsa [®] Loudspeaker Cables
Page 3	KáCsa [®] Microphone- / Guitar Cables
Page 4	KáCsa [®] Audio Interconnect Cables
Page 5	KáCsa [®] Digital- / Video Cables
Page 5	KáCsa [®] HDMI Cables
Page 6	KáCsa [®] VGA Cables
Page 6	KáCsa [®] Component video cables
Page 7	KáCsa [®] S-Video Cables
Page 7	KáCsa [®] SCART Cables
Page 7	KáCsa [®] Radio/(HD)TV coax Cables
Page 8	KáCsa [®] Wire
Page 8	KáCsa [®] Y-boots
Page 9	KáCsa [®] Snakeskin
Page 9	KáCsa [®] Shrink sleeves

Note: all listed cables are available per meter length.

Distributor: ELTIM audio BV, Eenrummerweg 5, NL-9961 PC Mensingeweer
Tel. +31 (0)595 491748 Fax. +31 (0)595 491946 info@eltim.eu

ELTIM[®]
AUDIO

www.eltim.eu

Loudspeaker Cable

KCELS075



The KáCsa® cables Expert Line 2 * 0,75 mm² OFC loudspeaker cable, made of 0,15 mm Ø wires with transparent PVC jacket.

KCELS15



The KáCsa® cables Expert Line 2 * 1,65 mm² OFC loudspeaker cable, made of 0,15 mm wires with transparent PVC jacket. Please note that 2 x 1,65 mm² is 10% more conductive copper than in standard 2 x 1,5mm² speaker cables.

KCELS25




The KáCsa® cables Expert Line 2 * 2,5 mm² OFC loudspeaker cable, made of 0,15 mm Ø wires with transparent PVC jacket.

KCELS40



The KáCsa® cables Expert Line 2 * 4 mm² OFC loudspeaker cable, made of 0,15 mm Ø wires with transparent PVC jacket.

KCELSW15



KáCsa Expert Line professional 2*1,5 mm² OFC speaker cable. The inner part of the cable made from 0,12 mm OFC wire, foamed PE layer for a perfect dumping and flexibility and pearl-white PVC outer jacket. Perfect solution for installers as well!

KCELSW25



KáCsa Expert Line professional 2*2,5 mm² OFC speaker cable. The inner part of the cable made from 0,12 mm OFC wire, foamed PE layer for a perfect dumping and flexibility and pearl-white PVC outer jacket. Perfect solution for installers as well!

KCEFL15



Very flat OFC speaker cable of the KáCsa® cables Expert Line. The flat geometry of the cable is reached by its interwoven (braided and not twisted) construction with 2 * 1,5 mm² cross section, in transparent clear PVC jacket. Ideal for cable runs under carpets or behind wall boards and well suited for all surround installations.

KCEFL25



Very flat OFC speaker cable of the KáCsa® cables Expert Line, the flat geometry of the cable is reached by its interwoven (braided and not twisted) construction with 2 * 2,5 mm² cross section, in transparent clear PVC jacket. Ideal for cable runs under carpets or behind wall boards and well suited for all surround installations.

KCEFL40



Very flat OFC speaker cable of the KáCsa® cables Expert Line, the flat geometry of the cable is reached by its interwoven (braided and not twisted) construction with 2 * 4 mm² cross section, in transparent clear PVC jacket. Ideal for cable runs under carpets or behind wall boards and well suited for all surround installations.

KCET40



OFC loudspeaker cable of the KáCsa® cables Expert Line. 2 * 4,08 mm² twisted OFC Time base corrected cable (three different diameters of copper wire to correct and compensate the various propagation velocities inside the cable) in transparent clear PVC jacket with blue XWD (extra wide center divider) center tab.

KCEBI40



The flat speaker cable of the KáCsa® cables, Expert Line, the 4 conductors are made from OFC braided (0,08 mm Ø wire) + multi gauge (0,12 mm Ø and 0,4 mm Ø) solid OFC wires resulting all together in a total of 2 * 4 mm² (2 * 2,32 mm² + 2 * 1,69 mm²), recommended and perfectly suited for both single an/or bi-wiring. The outer PVC jacket is dark grey color.

KCSLS15



Highly flexible 2 * 1,5 mm² loudspeaker cable of the KáCsa® cables Silver line, from thin silver plated copper (SPC) 0,1 mm Ø wires double insulation with inner foamed PE under the outer pearl white colored PVC jacket.

KCSFL075



Very flat 2 * 0,75 mm² loudspeaker cable of the KáCsa® cables, Silver line. The flat geometry of the cable is reached by its interwoven (braided and not twisted) construction with 2 * 0,75 mm² cross section, woven from thin silver plated copper (SPC) wires, in a clear transparent PVC jacket, with 3 mm transparent center divider tab. Ideal for cable runs under carpets or behind wall boards and well suited for all surround installations.

KCSFL15



Very flat 2 * 1,5 mm² loudspeaker cable of the KáCsa® cables, Silver line. The flat geometry of the cable is reached by its interwoven (braided and not twisted) construction with 2 * 1,5 mm² cross section, woven from thin silver plated copper (SPC) wires, in a clear transparent PVC jacket, with 3 mm transparent center divider tab. Ideal for cable runs under carpets or behind wall boards and well suited for all surround installations.

KC220



Stage type and PA (Public Address) KáCsa® loudspeaker cable with 2 * 2 mm² from OFC wires. The conductors are twisted together to reduce capacitance, the space between the cores and the jacket is filled up with cotton staples and paper foil. The dark blue round type PVC jacket is 8 mm Ø.

KC230



Stage type and PA (Public Address) KáCsa® loudspeaker cable with 2 * 3 mm² from OFC wires. The conductors are twisted together to reduce capacitance, the space between the cores and the jacket is filled up with cotton staples and paper foil. The dark blue round type PVC jacket is 9 mm Ø.

Microphone and Guitar Cable

KC066



Low loss – low capacity KáCsa® OFC microphone cable, symmetrical construction with blue and white PVC jacketed conductors of 2 * 0,215 mm². The conductors are twisted on each other to reduce capacitance and they are shielded by OFC spiral. The outer jacket is black PVC with 6 mm Ø.

The space between the outer jacket and the conductors is filled up with cotton staples and paper foil filament to reduce micro phonic noise.

KC088



KáCsa® guitar cable twisted from OFC wires, jacketed by white PVC and OFC spiral shielded. The black outer PVC jacket is 5,8 mm Ø. Cross section of the inner conductor is 0,23 mm².

Audio Interconnect Cable

KC020



High flexible single shielded (spiral) OFC mono KáCsa® audio interconnect cable in a black PVC jacket with 1,6 mm Ø.
The cross section of the internal OFC conductors is 0,11 mm².

KC022



High flexible single shielded (spiral) KáCsa® stereo audio interconnect cable with OFC conductors in black PVC jacket with 2 * 2,8 mm Ø.
The cross section of the internal OFC conductors is 2 * 0,11 mm².

KCE200



The stereo audio interconnect cable of the KáCsa® cables, Expert Line, OFC conductors, double shielded with a tight copper braiding plus and additional Aluminum Mylar foil shield.
The black outer foamed PVC jacket is 2 * 6 mm Ø.

KCS200



The stereo audio interconnect cable of the KáCsa® cables, Silver line. The balanced (symmetrical) cable has 2 solid silver plated copper (SPC) conductors with a cross section of 2 * 0,5 mm², double shielded with fully covering Aluminum Mylar foil and tight OFC braid, the space between the wires and the outer jacket is filled with cotton staples, the outer PVC jacket comes in elegant pearl white color measuring 8 mm Ø.
For your DIY assembly and cable termination we recommend and suggest the perfectly matching RP180GT8 type KáCsa® RCA plugs.

KCSXLR

No picture yet

No data yet

KCOSUB



Double shielded (Al-Mylar foil and OFC braid) symmetric audio interconnect cable of the KáCsa® cables Expert Line, made from solid core UP-OCC copper conductors with 0,8 mm² cross section, in a black PVC jacket, covered by tight black nylon „snake skin” mesh network.
The space between the twisted conductors is filled up with PP yarn.
8 mm Ø. We suggest to use this cable to drive subwoofers.

Digital / Video / Cable

KC100



Special KáCsa® cable for video/digital signal transmission with a correctly matching 75 Ohm impedance, 1 mm² OFC conductor (for long distance, too), double shielded (Alu foil and tinned copper braid) with dark blue outer PVC jacket of 8 mm Ø.

KCB100



The digital/video cable of the KáCsa® cables, Basic line with OFC conductor, double shielded with a tight spiral shield over a complete aluminium Mylar foils shielding. The Bordeaux red outer PVC jacket is 5 mm Ø.

KCE100



The digital/video cable of the KáCsa® cables, Expert line with OFC conductors (real 75 Ohm impedance) double shielded. The black outer foamed PVC jacket is 6 mm Ø.

KCS100



The digital/video cable of the KáCsa® cables, Silver line, 75 Ohm Silver plated copper (SPC) conductors, double shielded (Al Mylar foil and OFC braid), with 8 mm Ø pearl white color outer PVC jacket. For your DIY assembly and cable termination we recommend and suggest the perfectly matching RP180GT8 type KáCsa® RCA plugs.

HDMI cable

KCEHDMI

No picture yet

Special HDMI cable of KáCsa® Expert Line. Made from Solid Core OFC wires with a big 26 AWG! Certified as genuine HIGH SPEED HDMI® CABLE WITH ETHERNET (for length up to 5 m) and Certified as genuine STANDARD HDMI® CABLE WITH ETHERNET (for the length over 5 m) The cable is sold without HDMI plugs by meter on 50 m rolls and comes with a black outer jacket. For termination we recommend and suggest our KáCsa® DIY assembly HDMI connectors HDMIM.

KCSHDMI



Silver plated High End HDMI cable of KáCsa® Silver Line. Made from Silver plated Solid Core SPC wires with an impressively huge 24 AWG! Certified as genuine HIGH SPEED HDMI® CABLE WITH ETHERNET (for lengths up to 5 m) and Certified as genuine STANDARD HDMI® CABLE WITH ETHERNET (for the lengths over 5 m). The cable is sold without HDMI plugs by meter on 50 m rolls and comes with a black outer jacket. For termination we recommend and suggest our KáCsa® DIY assembly HDMI connectors HDMIM.

HDMItool



Professional crimping tool to mount our HDMIM connector to our KCEHDMI or KCSHDMI cables.

HDMItester



A set of HDMI cable testers with LED indication. With this set of testers you can check the functionality of a HDMI cable.

VGA cable

KCEVGA



VGA (DSUB) cable of the KáCsa® cables Expert Line, for video signal transmission, 5 * 75 Ohm cable twisted around cotton staples, with aluminum foil insulation and foamed, dark grey outer PVC jacket with 9 mm Ø.

KCSVGA



Professional VGA (DSUB) cable of the KáCsa® cables Expert Line for perfect video signal transmission, 5 * 75 Ohm silver plated copper (SPC) conductors, twisted around cotton staples, with Aluminum Mylar foil common and individual insulations in pearl white colored outer PVC jacket. 9 mm Ø.

Component Video cable

KCB300



The component cable of the KáCsa® cables, Basic line with 3 OFC conductors, each 75 Ohm, double shielded. The Bordeaux red colored outer PVC jacket measures 3 * 5 mm Ø.

KC300



KáCsa® component video/digital cable, double shielded (OFC braid, Al foil) with OFC conductors in PE foam insulation. Triple coaxial conductor construction with correct inner RGB (red, green, blue) color coding for error free channel identification and matching 75 Ohm impedance. The cross section of the inner conductors is 3 * 0,34 mm². The blue PVC outer jacket measures, 3 * 5,4 mm Ø.

KCE300



The KáCsa® cables Expert Line component cable with correct impedance matching 75 Ohm OFC conductors, double shielded with a tight copper mesh braiding plus a 100% covering Aluminum Mylar foil shield. The black outer PVC jacket is foamed and measures 3 * 6 mm Ø.

KCS300



High End component cable of the KáCsa® cables, Silver line with correct impedance matching 75 Ohm Silver plated copper (SPC) conductor, double shielded with a 100% covering Aluminum Mylar foil and a tight SPC spiral shielding, elegant pearl white colored outer PVC jacket measuring 3*6 mm. For your DIY assembly and cable termination we recommend and suggest to the RP 180GT6 (red, green and blue coded) type of KáCsa® RCA plugs.

S-video cable

KCES542



Triple shielded (OFC braid, Al foil and tinned copper braid) true 75 Ohm high quality SVHS cable with OFC conductors, with dark grey foamed outer PVC jacket, 8 mm Ø.

KCES



The S-video cable of the KáCsa® cables Expert line, correctly matching 75 Ohm impedance of the 4 OFC conductors with terracotta colored insulation. The outer foamed PVC jacket is 8 mm Ø.

KCSS



The professional SVHS cable of the KáCsa® cables, Silver line, correctly matching 75 Ohm. Silver plated copper (SPC) conductors of 2 * 0,43 mm² cross section, double shielded with a fully covering Aluminum Mylar foil and tight OFC braid. The space between the wires and the jacket is filled with cotton staples. Pearl white colored outer PVC jacket with 8,3 mm Ø. For your DIY assembly and cable termination we recommend and suggest to use the SVHS6 type of KáCsa® SVHS plugs.

SCART cable

KCBSC



The KáCsa® cables Basic Line SCART Audio/Video cable with OFC conductors (for the fully loaded 21 pin contacts) and shield, 75 Ohm video signal wires. The Bordeaux red outer PVC jacket is 9 mm Ø, matching perfectly to the SC1G or SC2G type KáCsa® SCART connectors.

KCESC



Professional SCART cable of the KáCsa® cables Expert Line. OFC conductors for all 21 pin SCART connection, the black outer jacket is made from foamed PVC. For your DIY assembly and termination we suggest and recommend to use the perfectly matching SC1G or SC2G type KáCsa® SCART connectors.

KCSSC



The professional SCART A/V cable of the KáCsa® cables, Silver line, with correctly matched 75 Ohm Silver plated copper (SPC) conductors for all 21 contact pins, double shielded with 11 Ø mm pearl white colored outer PVC jacket. For your DIY assembly and cable termination we recommend and suggest to the SC1G type KáCsa® SCART plugs.

Radio / TV Antenna cable

KCEHDTV



Special HDTV antenna (coax) cable of the KáCsa® cables Expert Line, correct 75 Ohm impedance matching with a solid core OFC conductor (1mm Ø diameter) and quadruple (4x) shield (aluminum foil/tinned copper braid/aluminum foil/tinned copper braid) which results in an extraordinary **120 dB shield rejection**. The grey color outer PVC jacket is 7 mm Ø. For DIY self assembly we recommend and suggest: for F-type connection: F17 plug and for Radio/TV connection: TV1101G (male) and TV1102G (female) plugs.

Wire

HUW0,8 0,8 mm² UP-OCC mono crystal solid copper (Hook-Up-Wire)



HUW1,3 1,3 mm² UP-OCC mono crystal solid copper (Hook-Up-Wire)



HUW2,1 2,1 mm² UP-OCC mono crystal solid copper (Hook-Up-Wire)



HUW3,3 3,3 mm² UP-OCC mono crystal solid copper (Hook-Up-Wire)



SHUW 0,31 mm² pure silver hook-up wire for internal wiring with teflon insulation, Ø 1 mm.



Y-Boots

LSVS Y-boot black or red soft PVC for the termination of symmetrical audio interconnect cables or coaxial type loudspeaker cables.



Inlet: 6 mm Ø, length of the branches is 45 mm with outlets of 3 mm Ø.

LSVL8 Y-boot black or red soft PVC for the termination of symmetrical audio interconnect cables or coaxial type loudspeaker cables.



Inlet 8 mm Ø, length of the branches is 45 mm with outlets of 3 mm Ø

LSVX Y-boot black or red soft PVC for the termination of symmetrical audio interconnect cables or coaxial type loudspeaker cables.



Inlet 13 mm Ø, length of the branches is 55 mm with outlets of 5 mm Ø.

LSVXL Y-boot black or red soft PVC for the termination of symmetrical audio interconnect cables or coaxial type loudspeaker cables.



Inlet 15 mm Ø, length of the branches is 60 mm with outlets of 6 mm Ø.

Snakeskin

ES204818



For cables up to Ø 6.5mm ~ 12.5mm.
NOTE: the sleeve doesn't shrink due to heat, just stretch it over the cable.

Polyester braided, high temperature-resistant, used for protecting cable.
This version also available with white color!

ES304820K



For cables up to Ø 8.5mm ~ 15.0mm.
NOTE: the sleeve doesn't shrink due to heat, just stretch it over the cable.

Polyester braided, high temperature-resistant, used for protecting cable.

ES304820F



For cables up to Ø 8.5mm ~ 15.0mm.
NOTE: the sleeve doesn't shrink due to heat, just stretch it over the cable.

Polyester braided, high temperature-resistant, used for protecting cable.

ES304818



For cables up to Ø 8.5mm ~ 15.0mm.
NOTE: the sleeve doesn't shrink due to heat, just stretch it over the cable.

Polyester braided, high temperature-resistant, used for protecting cable.
This version also available with white color!

ES406420



For cables up to Ø 23.0mm ~ 30.0mm.
NOTE: the sleeve doesn't shrink due to heat, just stretch it over the cable.

Polyester braided, high temperature-resistant, used for protecting cable.
This version also available with white color!

Schink sleeves

HSHT2,5

Heat shrinkable tube Ø 2,5mm.
Available in different colors in 1 meter lengths.

HSHT3,5

Heat shrinkable tube Ø 3,5mm.
Available in different colors in 1 meter lengths.

HSHT5,0

Heat shrinkable tube Ø 5,0mm.
Available in different colors in 1 meter lengths.

HSHT7,0



Heat shrinkable tube Ø 7,0mm.
Available in different colors in 1 meter lengths.

HSHT10

Heat shrinkable tube Ø 10mm.
Available in different colors in 1 meter lengths.

HSHT15

Heat shrinkable tube Ø 15mm.
Available in different colors in 1 meter lengths.

HSHT18

Heat shrinkable tube Ø 18mm.
Available in different colors in 1 meter lengths.

HSHT25

Heat shrinkable tube Ø 25mm.
Available in different colors in 1 meter lengths.